



VT8 light tower

The compact footprint and ease of use are two main features that make the **VT8 light tower** one of the top models in the Generac Mobile[®] range. High performance balanced with low cost allowed the VT8 to became the best-seller model in the extra-European market.

THE BEST SELLER

The VT8 is **the best seller model** of light tower in the extra-european market, thanks to the vertical mast and the high quality features granted by Generac Mobile[®].

Vertical mast

A **telescopic vertical mast** with manual lifting system and a maximum height of 8 meters.

Metal halide lamps

4x1000W powerful metal halide lamps able to illuminate medium and big working areas.

Trailer options

The VT8 is equipped as standard with a **low speed trailer** but it can be also mounted on a **straight road trailer**.

Engine options

You can choose the engine you prefer between between Yanmar 3TN and Kubota D1105.



Picture shown may not reflect actual configuration.





VT8 K3	Technical Data
Minimum dimensions (L x W x H)	2650 x 1300 x 2460 mm
Maximum dimensions (L x W x H)	2650 x 2460 x 8000 mm
Dry weight	716 kg
Lifting system	Manual
Mast rotation	340°
Lamps power	4 x 1000 W
Lamps type	МН
Total lumen	360000 Lm
Illuminated area	4200 m ²
Engine	Kubota D1105
Engine cooling	Liquid
Cylinders (q.ty)	3
Engine speed (50/60 Hz)	1500 / 1800 rpm
Liquid containment (110%)	No
Alternator (kVA/V/Hz)	8/220/50 — 8/240/60
Outlet socket (kVA/V/Hz)	3/220/50 – 3/240/60
Avg. sound pressure	68 dB(A) @ 7m
Wind speed resistance	110 km/h
Tank capacity	75
Running time	44 h



Picture shown may not reflect actual configuration.